



SGM4562Q

Automotive, 4-Bit Bidirectional Voltage-Level Translator with Automatic Direction Sensing

GENERAL DESCRIPTION

The SGM4562Q is a 4-bit, non-inverting, bidirectional voltage-level translator which features two independent configurable power supply lines. The A and B ports track the V_{CCA} supply and V_{CCB} supply respectively. The supply voltage range is 1.2V to 3.6V for A ports and 1.65V to 5.5V for B ports. The device provides a bidirectional translation function among different voltage nodes (including 1.2V, 1.5V, 1.8V, 2.5V, 3.3V and 5V).

The SGM4562Q has an output-enabled (OE) function, which controls the outputs states. When OE goes low, all outputs enter into the high-impedance state. The OE should be connected to GND via a pull-down resistor, and the minimum resistor value depends on the current source capability of the driver.

The device is AEC-Q100 qualified (Automotive Electronics Council (AEC) standard Q100 Grade 1) and it is suitable for automotive applications.

The SGM4562Q is available in Green TSSOP-14, UTQFN-1.7×2-12L and TQFN-2.5×3-14L packages. It operates over an ambient temperature range of -40°C to +125°C.

FEATURES

- AEC-Q100 Qualified for Automotive Applications Device Temperature Grade 1
 $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$
- Power Supply Voltage Ranges ($V_{CCA} \leq V_{CCB}$)
 - ♦ A Ports: 1.2V to 3.6V
 - ♦ B Ports: 1.65V to 5.5V
- Support V_{CCA} or V_{CCB} Isolation
 - ♦ When V_{CCA} or V_{CCB} is Low, Device Enters Power-Down Mode
- OE Input Tracks the V_{CCA} Supply
- Low Power Consumption
- Support Partial-Power-Down Function
- -40°C to +125°C Operating Temperature Range
- Available in Green TSSOP-14, UTQFN-1.7×2-12L and TQFN-2.5×3-14L Packages

APPLICATIONS

- Automotive Applications
- Industrial Equipment
- Smartphones
- Portable Equipment
- Medical Equipment

TYPICAL APPLICATION




Figure 1. Typical Application Circuit

Automotive, 4-Bit Bidirectional Voltage-Level Translator with Automatic Direction Sensing

SGM4562Q

PACKAGE/ORDERING INFORMATION


MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE TOP MARKING	PACKING OPTION
SGM4562Q	TSSOP-14	-40°C to +125°C	SGM4562QTS14G/TR	1MX TS14 XXXXX	Tape and Reel, 4000
	UTQFN-1.7×2-12L	-40°C to +125°C	SGM4562QURF12G/TR	1FV XXXXY	Tape and Reel, 3000
	TQFN-2.5×3-14L	-40°C to +125°C	SGM4562QTWB14G/TR	20UWB XXXXX XX#XX	Tape and Reel, 3000

MARKING INFORMATION


NOTE: XXX = Date Code and Trace Code. XXXXX = Date Code, Trace Code and Vendor Code. XX#XX = Coordinate Information and Wafer ID Number.

TSSOP-14


XXXXX



UTQFN-1.7×2-12L



TQFN-2.5×3-14L



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

Automotive, 4-Bit Bidirectional Voltage-Level Translator with Automatic Direction Sensing

SGM4562Q

ABSOLUTE MAXIMUM RATINGS

Supply Voltage Range	
V_{CCA}	-0.5V to 4.6V
V_{CCB}	-0.5V to 6.0V
Input Voltage Range, V_I	
A Ports	-0.5V to 4.6V
B Ports	-0.5V to 6.0V
Output Voltage Range for the High-Impedance or Power-Down State, V_O	
A Ports	-0.5V to 4.6V
B Ports	-0.5V to 6.0V
Output Voltage Range for the High or Low State, V_O ⁽¹⁾	
A Ports	-0.5V to $V_{CCA} + 0.5V$
B Ports	-0.5V to $V_{CCB} + 0.5V$
Input Clamp Current, I_{IK} ($V_I < 0$)	-50mA (MAX)
Output Clamp Current, I_{OK} ($V_O < 0$)	-50mA (MAX)
Continuous Output Current, I_O	-50mA to 50mA
Continuous Current through V_{CCA} , V_{CCB} , or GND	
.....	-100mA to 100mA
Package Thermal Resistance	
TSSOP-14, θ_{JA}	131.2°C/W
TSSOP-14, θ_{JB}	91.4°C/W
TSSOP-14, θ_{JC}	60.9°C/W
UTQFN-1.7×2-12L, θ_{JA}	135.1°C/W
UTQFN-1.7×2-12L, θ_{JB}	56.6°C/W
UTQFN-1.7×2-12L, θ_{JC}	80.2°C/W
TQFN-2.5×3-14L, θ_{JA}	55.7°C/W
TQFN-2.5×3-14L, θ_{JB}	26.4°C/W
TQFN-2.5×3-14L, θ_{JC} (TOP)	59.8°C/W
TQFN-2.5×3-14L, θ_{JC} (BOT)	10.6°C/W
Junction Temperature	+150°C
Storage Temperature Range	-65°C to +150°C
Lead Temperature (Soldering, 10s)	+260°C
ESD Susceptibility ^{(2) (3)}	
HBM	±7000V
CDM	±1000V

NOTES:

- V_{CCA} and V_{CCB} values are shown in the Recommended Operating Conditions table.
- For human body model (HBM), all pins comply with AEC-Q100-002 specification.
- For charged device model (CDM), all pins comply with AEC-Q100-011 specification.

RECOMMENDED OPERATING CONDITIONS ^{(4) (5)}

Supply Voltage Range	
V_{CCA}	1.2V to 3.6V
V_{CCB}	1.65V to 5.5V

High-Level Input Voltage, V_{IH}	
Data Inputs ($V_{CCA} = 1.2V$ to $3.6V$, $V_{CCB} = 1.65V$ to $5.5V$) $V_{CCI} \times 0.65$ ⁽⁶⁾ to V_{CCI}
OE Input ($V_{CCA} = 1.2V$ to $3.6V$, $V_{CCB} = 1.65V$ to $5.5V$) $V_{CCA} \times 0.65$ to $5.5V$
Low-Level Input Voltage, V_{IL}	
Data Inputs ($V_{CCA} = 1.2V$ to $3.6V$, $V_{CCB} = 1.65V$ to $5.5V$) $0V$ to $V_{CCI} \times 0.35$ ⁽⁶⁾
OE Input ($V_{CCA} = 1.2V$ to $3.6V$, $V_{CCB} = 1.65V$ to $5.5V$) $0V$ to $V_{CCA} \times 0.35$
Output Voltage Range for the High-Impedance or Power-Down State, V_O	
A Ports	$0V$ to $3.6V$
B Ports	$0V$ to $5.5V$
Input Transition Rise or Fall Rate, $\Delta t/\Delta V$	
A Port Inputs ($V_{CCA} = 1.2V$ to $3.6V$, $V_{CCB} = 1.65V$ to $5.5V$) 40ns/V (MAX)
B Port Inputs ($V_{CCA} = 1.2V$ to $3.6V$, $V_{CCB} = 1.65V$ to $5.5V$) 40ns/V (MAX)
Operating Temperature Range	
.....	-40°C to +125°C

NOTES:

- Ensure that the A side and B side of the unused data I/O pairs remain the same state, that is, both at V_{CCI} or both at GND.
- Ensure that $V_{CCA} \leq V_{CCB}$ and V_{CCA} must not exceed 3.6V.
- V_{CCI} is the supply voltage associated with the input ports.

OVERSTRESS CAUTION

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.




ESD SENSITIVITY CAUTION

This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

PIN CONFIGURATIONS



PIN DESCRIPTION

PIN			NAME	TYPE	FUNCTION
TSSOP-14	UTQFN-1.7x2-12L	TQFN-2.5x3-14L			
1	1	1	V _{CCA}	P	Supply Voltage on A Ports. It can be operated from 1.2V to 3.6V.
2, 3, 4, 5	2, 3, 4, 5	2, 3, 4, 5	A1, A2, A3, A4	I/O	Data Inputs/Outputs. These pins track the V _{CCA} supply.
6, 9	—	6, 9	NC	—	No Connection.
7	6	7	GND	G	Ground.
8	12	8	OE	I	Output-Enabled Input. When OE goes low, all outputs enter into high-impedance state. It tracks the V _{CCA} supply.
10, 11, 12, 13	7, 8, 9, 10	10, 11, 12, 13	B4, B3, B2, B1	I/O	Data Inputs/Outputs. These pins track the V _{CCB} supply.
14	11	14	V _{CCB}	P	Supply Voltage on B Ports. It can be operated from 1.65V to 5.5V.
—	—	Exposed Pad	EP	—	Exposed Pad. It can be connected to GND or be left floating.

NOTE: I = input, I/O = input/output, P = power, G = ground.

SGM4562Q Automotive, 4-Bit Bidirectional Voltage-Level Translator with Automatic Direction Sensing

FUNCTIONAL BLOCK DIAGRAM





Figure 2. Architecture of SGM4562Q I/O Cell

PACKAGE OUTLINE DIMENSIONS

UTQFN-1.7×2-12L





Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	0.450	-	0.550
A1	0.000	-	0.050
A2	0.152 REF		
b	0.150	-	0.250
D	1.600	-	1.800
E	1.900	-	2.100
e	0.400 BSC		
L	0.450	-	0.550
L1	0.150 REF		
eee	0.080		



NOTE: This drawing is subject to change without notice.

PACKAGE OUTLINE DIMENSIONS

TSSOP-14



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	-	-	1.200
A1	0.050	-	0.150
A2	0.800	-	1.050
b	0.190	-	0.300
c	0.090	-	0.200
D	4.860	-	5.100
E	4.300	-	4.500
E1	6.200	-	6.600
e	0.650 BSC		
L	0.450	-	0.750
H	0.250 TYP		
θ	0°	-	8°
ccc	0.100		


NOTES:

1. This drawing is subject to change without notice.
2. The dimensions do not include mold flashes, protrusions or gate burrs.
3. Reference JEDEC MO-153.

PACKAGE INFORMATION

PACKAGE OUTLINE DIMENSIONS

TQFN-2.5×3-14L




Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	0.700	-	0.800
A1	0.000	-	0.050
A2	0.203 REF		
b	0.200	-	0.300
D	2.400	-	2.600
D1	0.900	-	1.100
E	2.900	-	3.100
E1	1.400	-	1.600
e	0.500 BSC		
k	0.350 REF		
L	0.300	-	0.500
eee	0.080		

NOTE: This drawing is subject to change without notice.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
UTQFN-1.7×2-12L	7"	9.5	1.90	2.30	0.75	4.0	4.0	2.0	8.0	Q1
TSSOP-14	13"	12.4	6.80	5.40	1.50	4.0	8.0	2.0	12.0	Q1
TQFN-2.5×3-14L	13"	12.4	2.80	3.30	1.15	4.0	4.0	2.0	12.0	Q1

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
7" (Option)	368	227	224	8
7"	442	410	224	18
13"	386	280	370	5

DD0002