

### FEATURES

- Low On-State Resistance
- Low Total Gate Charge and Capacitance Losses
- RoHS Compliant and Halogen Free

### PRODUCT SUMMARY

$R_{DS(on)}$ (TYP) $V_{GS} = 10V$	$R_{DS(on)}$ (MAX) $V_{GS} = 10V$	$I_D$ (MAX) $T_C = +25^\circ C$
0.7m $\Omega$	0.95m $\Omega$	230A

### ABSOLUTE MAXIMUM RATINGS


PARAMETER	SYMBOL	VALUE	UNITS
Drain-to-Source Voltage	$V_{DS}$	30	V
Gate-to-Source Voltage	$V_{GS}$	$\pm 20$	V
Drain Current <sup>(1)</sup>	$I_D$	$T_C = +25^\circ C$	230
		$T_C = +100^\circ C$	140
		$T_A = +25^\circ C$	37
		$T_A = +70^\circ C$	29
Drain Current (Pulse) <sup>(2)</sup>	$I_{DM}$	900	A
Total Dissipation	$P_D$	$T_C = +25^\circ C$	96
		$T_C = +100^\circ C$	38
		$T_A = +25^\circ C$	2.5
		$T_A = +70^\circ C$	1.6
Avalanche Current <sup>(3)</sup>	$I_{AS}$	83	A
Avalanche Energy <sup>(3)</sup>	$E_{AS}$	344.5	mJ
Junction Temperature	$T_J$	+150	$^\circ C$
Storage Temperature Range	$T_{STG}$	-55 to +150	$^\circ C$
Lead Temperature (Soldering, 10s)		+260	$^\circ C$

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability.


**NOTES:**

1. The current will be limited by PCB, thermal design and operating temperature.
2.  $t_{PLUSE} < 10\mu s$ .
3. Parts are 100% tested at  $V_{GS} = 10V$ ,  $I_L = 59A$ , and  $E_{AS} = 174.05mJ$ .

### PIN CONFIGURATION



### EQUIVALENT CIRCUIT



### APPLICATIONS

- CPU Power Delivery
- DC/DC Converters
- Power Load Switch
- Notebook Battery Management


**PACKAGE/ORDERING INFORMATION**

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGMNQ09430	PDFN-5×6-8BL	-55°C to +150°C	SGMNQ09430TPDA8G/TR	SGM1L0 TPDA8 XXXXX	Tape and Reel, 4000

**MARKING INFORMATION**

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.

**XXXXX**



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

**DISCLAIMER**

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

**THERMAL RESISTANCE**







PARAMETER	SYMBOL	TYP	UNITS
Junction-to-Case Thermal Resistance	$R_{\theta JC}$	1.3	°C/W
Junction-to-Ambient Thermal Resistance <sup>(1)</sup>	$R_{\theta JA}$	49	°C/W

NOTE: 1.  $R_{\theta JA}$  is determined with the device mounted on one square inch of copper pad, 2oz copper on FR4 board.







**ELECTRICAL CHARACTERISTICS**(T<sub>A</sub> = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
<b>Static OFF Characteristics</b>						
Drain-to-Source Breakdown Voltage	V <sub>BR_DSS</sub>	V <sub>GS</sub> = 0V, I <sub>D</sub> = 250μA	30			V
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 24V			2	μA
Gate-to-Source Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V			±100	nA
<b>Static ON Characteristics</b>						
Gate-to-Source Threshold Voltage	V <sub>GS_TH</sub>	V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 250μA	1.2	1.5	2.2	V
Drain-to-Source On-State Resistance	R <sub>DS(on)</sub>	I <sub>D</sub> = 30A	V <sub>GS</sub> = 10V	0.7	0.95	mΩ
			V <sub>GS</sub> = 4.5V	1.0	1.45	
Forward Transconductance	g <sub>FS</sub>	V <sub>DS</sub> = 12V, I <sub>D</sub> = 15A		30		S
Gate Resistance	R <sub>G</sub>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 0V, f = 1MHz		1.5		Ω
<b>Diode Characteristics</b>						
Diode Forward Voltage	V <sub>F_SD</sub>	V <sub>GS</sub> = 0V, I <sub>S</sub> = 10A		0.7	1.2	V
Reverse Recovery Time	t <sub>RR</sub>	V <sub>GS</sub> = 0V, I <sub>S</sub> = 30A, di/dt = 100A/μs		90		ns
Reverse Recovery Charge	Q <sub>RR</sub>			125		nC
<b>Dynamic Characteristics</b>						
Input Capacitance	C <sub>ISS</sub>	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 15V, f = 1MHz		5280		pF
Output Capacitance	C <sub>OSS</sub>			2320		
Reverse Transfer Capacitance	C <sub>RSS</sub>			280		
Total Gate Charge	Q <sub>G</sub>	V <sub>DS</sub> = 15V, I <sub>D</sub> = 30A	V <sub>GS</sub> = 10V	99		nC
			V <sub>GS</sub> = 4.5V	50		
Gate-to-Source Charge	Q <sub>GS</sub>	V <sub>GS</sub> = 4.5V, V <sub>DS</sub> = 15V, I <sub>D</sub> = 30A		18		nC
Gate-to-Drain Charge	Q <sub>GD</sub>			22		
<b>Switch Characteristics</b>						
Turn-On Delay Time	t <sub>D_ON</sub>	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 15V, I <sub>D</sub> = 15A, R <sub>G</sub> = 3Ω		13		ns
Rise Time	t <sub>R</sub>			38		
Turn-Off Delay Time	t <sub>D_OFF</sub>			67		
Fall Time	t <sub>F</sub>			51		


TYPICAL PERFORMANCE CHARACTERISTICS



TYPICAL PERFORMANCE CHARACTERISTICS (continued)



TYPICAL PERFORMANCE CHARACTERISTICS (continued)



REVISION HISTORY


NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Original to REV.A (APRIL 2026)	Page
Changed from product preview to production data.....	All

# PACKAGE INFORMATION

## PACKAGE OUTLINE DIMENSIONS

### PDFN-5×6-8BL



RECOMMENDED LAND PATTERN (Unit: mm)


Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	1.000	1.100	1.200
b	0.300	0.400	0.500
c	0.150	0.250	0.350
D	4.800	-	5.400
D1	4.800	4.900	5.000
D2	3.910	4.010	4.310
E	5.900	6.000	6.250
E1	5.650	5.750	5.850
E2	3.300	3.440	3.540
e	1.270 BSC		
H	0.350	0.610	0.710
k	1.100	-	-
L	0.380	0.610	0.710
L1	0.050	0.130	0.250
L2	-	-	0.220
θ	8°	10°	12°

NOTE: This drawing is subject to change without notice.


# PACKAGE INFORMATION

## TAPE AND REEL INFORMATION

### REEL DIMENSIONS



### TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

### KEY PARAMETER LIST OF TAPE AND REEL


Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
PDFN-5×6-8BL	13"	12.4	6.45	5.30	1.40	4.0	8.0	2.0	12.0	Q1

DD0001



# PACKAGE INFORMATION

## CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

## KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

DD0002