

FEATURES

- High-Speed Switching
- Low On-State Resistance
- RoHS Compliant and Halogen Free

ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	VALUE	UNITS
Drain-to-Source Voltage	V_{DS}	-30	V
Gate-to-Source Voltage	V_{GS}	± 20	V
Drain Current ⁽¹⁾	I_D	$T_C = +25^\circ\text{C}$	-60
		$T_C = +100^\circ\text{C}$	-38
		$T_A = +25^\circ\text{C}$	-11
		$T_A = +70^\circ\text{C}$	-9
Drain Current (Pulse) ⁽²⁾	I_{DM}	-150	A
Total Dissipation	P_D	$T_C = +25^\circ\text{C}$	62
		$T_C = +100^\circ\text{C}$	25
		$T_A = +25^\circ\text{C}$	2.2
		$T_A = +70^\circ\text{C}$	1.4
Avalanche Current ⁽³⁾	I_{AS}	-50.9	A
Avalanche Energy ⁽³⁾	E_{AS}	129.6	mJ
Junction Temperature	T_J	+150	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150	$^\circ\text{C}$
Lead Temperature (Soldering, 10s)		+260	$^\circ\text{C}$

Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

NOTES:


1. The current will be limited by PCB, thermal design and operating temperature.
2. $t_{PULSE} < 10\mu\text{s}$.
3. Parts are 100% tested at $V_{GS} = -10\text{V}$, $I_L = -36\text{A}$, and $E_{AS} = 64.8\text{mJ}$.

PRODUCT SUMMARY

$R_{DS(on)}$ (TYP) $V_{GS} = -10\text{V}$	$R_{DS(on)}$ (MAX) $V_{GS} = -10\text{V}$	I_D (MAX) $T_C = +25^\circ\text{C}$
6.5m Ω	8.1m Ω	-60A


PIN CONFIGURATION

(TOP VIEW)



PDFN-3.3x3.3-8AL

EQUIVALENT CIRCUIT



APPLICATIONS

- Relay Driver Application
- Load Switch Application
- High-Speed Line Driver
- Handheld and Mobile Application
- USB Connector VBUS Power Switch
- IR Blaster Application


PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
SGMPM07330	PDFN-3.3x3.3-8AL	-55°C to +150°C	SGMPM07330TPDB8G/TR	SGM24D TPDB8 XXXXXX	Tape and Reel, 5000

MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.

XXXXX



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

THERMAL RESISTANCE

PARAMETER	SYMBOL	TYP	UNITS
Junction-to-Case Thermal Resistance	$R_{\theta JC}$	2	°C/W
Junction-to-Ambient Thermal Resistance ⁽¹⁾	$R_{\theta JA}$	56	°C/W







NOTE: 1. $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, 2oz copper on FR4 board.

ELECTRICAL CHARACTERISTICS







(T_A = +25°C, unless otherwise noted.)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Static OFF Characteristics						
Drain-to-Source Breakdown Voltage	V _{BR_DSS}	V _{GS} = 0V, I _D = -250μA	-30			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{GS} = 0V, V _{DS} = -24V			-1	μA
Gate-to-Source Leakage Current	I _{GSS}	V _{GS} = ±20V, V _{DS} = 0V			±100	nA
Static ON Characteristics						
Gate-to-Source Threshold Voltage	V _{GS_TH}	V _{GS} = V _{DS} , I _D = -250μA	-1.0	-1.6	-2.5	V
Drain-to-Source On-State Resistance	R _{DS(on)}	V _{GS} = -10V, I _D = -20A		6.5	8.1	mΩ
		V _{GS} = -4.5V, I _D = -15A		9.5	12.4	
Forward Transconductance	g _{FS}	V _{DS} = -5V, I _D = -15A		38		S
Gate Resistance	R _G	V _{GS} = 0V, V _{DS} = 0V, f = 1MHz		6.4		Ω
Diode Characteristics						
Diode Forward Voltage	V _{F_SD}	V _{GS} = 0V, I _S = -1A		-0.7	-1.0	V
Reverse Recovery Time	t _{RR}	V _{GS} = -10V, I _S = -15A, di/dt = 100A/μs		17		ns
Reverse Recovery Charge	Q _{RR}			9		nC
Dynamic Characteristics						
Input Capacitance	C _{ISS}	V _{GS} = 0V, V _{DS} = -15V, f = 1MHz		2750		pF
Output Capacitance	C _{OSS}			328		
Reverse Transfer Capacitance	C _{RSS}			296		
Total Gate Charge	Q _G	V _{DS} = -15V, I _D = -15A	V _{GS} = -10V	55.5		nC
			V _{GS} = -4.5V	27.2		
Gate-to-Source Charge	Q _{GS}	V _{GS} = -4.5V, V _{DS} = -15V, I _D = -15A		8.1		nC
Gate-to-Drain Charge	Q _{GD}			12		
Switch Characteristics						
Turn-On Delay Time	t _{D_ON}	V _{GS} = -10V, V _{DS} = -15V, I _D = -15A, R _G = 3Ω		7.6		ns
Rise Time	t _R			36		
Turn-Off Delay Time	t _{D_OFF}			123		
Fall Time	t _F			64		


TYPICAL PERFORMANCE CHARACTERISTICS



TYPICAL PERFORMANCE CHARACTERISTICS (continued)



TYPICAL PERFORMANCE CHARACTERISTICS (continued)




REVISION HISTORY

NOTE: Page numbers for previous revisions may differ from page numbers in the current version.

Changes from Original to REV.A (MAY 2026)	Page
Changed from product preview to production data.....	All

PACKAGE OUTLINE DIMENSIONS

PDFN-3.3×3.3-8AL



RECOMMENDED LAND PATTERN (Unit: mm)


Symbol	Dimensions In Millimeters		
	MIN	NOM	MAX
A	0.700	0.800	0.900
b	0.250	0.300	0.350
c	0.140	0.150	0.200
D	3.100	3.300	3.500
D1	3.050	3.150	3.250
D2	2.350	2.450	2.550
E	3.100	3.300	3.500
E1	2.900	3.000	3.100
E2	1.640	1.740	1.840
e	0.650 BSC		
H	0.320	0.420	0.520
k	0.590	0.690	0.790
L	0.250	0.400	0.550
L1	0.100	0.150	0.200
L2	-	-	0.150
θ	8°	10°	12°

NOTE: This drawing is subject to change without notice.


PACKAGE INFORMATION

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
PDFN-3.3×3.3-8AL	13"	12.4	3.60	3.60	1.10	4.0	8.0	2.0	12.0	Q1

DD0001

PACKAGE INFORMATION

CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

DD0002